

I N S P I R E D B Y

TERRAINS

30x20cm & 20x20cm

CONN^ECA
COLLECTION




GLOBAL

INSPIRED BY TERRAINS

Presenting Conneca by R Global, a collection of tough pavers in 30x20cm and 20x20cm sizes and 2cm thickness that redefines strength, solidity, soundness, and stability. The collection is inspired by resilient and enduring natural terrains and offers modern spaces a perfect tiling solution that blends form and functionality.



A HERITAGE THAT APPLAUDS INTRICACY





GREETINGS | FOUNDER

Conceptualized under a vision to see the Indian and Global ceramic industry excel through its various verticals, R Global was founded to fill the interlude and build an arch between ceramic & homedecor world manufacturers, distributors, and end-users through meticulously designed sourcing services.

With expert knowledge of the industry, R Global aims to provide precise and cost-efficient ceramic & homedecor sourcing services globally connecting and assisting distributors with companies and end-users to the right products after assessing their needs.

R Global will be a one-stop destination providing the need-based, versatile, and comprehensive tiling solution in-housing a wide range of ceramic & homedecor products from leading manufacturers from around the world. It will also be entertaining all ceramic & homedecor sourcing services you need for your dream project.

Feel at ease with R Global, where ceramics and homedecor turn to stories and craft a narrative of excellence in every corner.

Mr. Chetan R. Patel



VISION

To become global sourcing and servicing leaders in the ceramic & home decor world.



MISSION

To fill the gap and build bridges through knowledge & exceptional services in the ceramic and home decor world.




THE WORLD OF
CERAMICS &
HOME DECOR



G L O B A L



MODERN-AGE
LIFESTYLE
SOLUTIONS



SOURCING
PROFESSIONAL
SERVICING /
SOURCING OF
QUALITY PRODUCTS



SERVICE
A KEY FACTOR
FOR R GLOBAL



TAKING
INNOVATIONS
TO
THE NEXT STEP

FEATURES

RESILIENT FEATURES FOR RESISTANT SPACES



UV RESISTANT



SCRATCH
RESISTANT



RESISTANT TO
THERMAL SHOCK



DIMENSIONAL
STABILITY



RESISTANT TO HEAT &
HIGH TEMPERATURES



EASY TO CLEAN
AND MAINTAIN



ANTI - SKID
SURFACE



RESISTANT
TO STAINING



HYGIENIC
SURFACE

The exclusive collection is rich in resilient features, boosting unmatched strength and resilience. It offers you resistant spaces that withstand harsh conditions and are low-maintenance. The pavers resist high temperatures, scratches, stains, and more while offering an anti-skid surface so you can move worry-free.


APPLICATION AREAS

The collection's features, tough build, and functional dimension offer extensive application opportunities in spaces that defy harsh conditions. With Conneca pavers, you can effortlessly transform your outdoor areas, swimming pool borders and decks, gardens, walls, stairs, pavements, and more.


AVAILABLE SIZES: 20x30cm | 20x20cm



OUTDOOR &
SIT OUT AREA



PATHWAYS



SWIMMING POOL
BORDER



GARDENS



PATIOS



STAIRS



TERRACES



WALL



URBAN PAVEMENT




GLOBAL



2001

Finish: Matt | Thickness: 2cm



The Epitome Of Durability And Style



GLOBAL




2005

Finish: Matt | Thickness: 2cm



Enhancing Your Outdoors With Durability




2002
Finish: Matt | Thickness: 2cm

Witness Originality Through Our Patterns




2004
 Finish: Matt | Thickness: 2cm

The Strongest Force Of your space



2006
 Finish: Matt | Thickness: 2cm

Crafting Timeless Memories In Every Corner




2005
Finish: Matt | Thickness: 2cm

Bringing Elegance To Your Outdoors



2007
 Finish: Matt | Thickness: 2cm

Unmatched Strength. Unmatched Style




2008
 Finish: Matt | Thickness: 2cm

inspiring Simplicity With Our Designs



2010
Finish: Matt | Thickness: 2cm



Enhance Your Outdoors With Simplicity




2011
Finish: Matt | Thickness: 2cm





Unmatched Standard Of Strength & Impact




2012
 Finish: Matt | Thickness: 2cm



The Robust Way Of An Innovative Style



2015
 Finish: Matt | Thickness: 2cm



Creating A Blend Of Strength & Style

TECHNICAL SPECIFICATION

PACKING DETAILS						
Size	200x200mm			200x300mm		
Thikness	15mm	20mm	30mm	15mm	20mm	30mm
Pcs / Box	13	10	7	8	6	4
Weight / Box	18	18	19	16.6	16.6	16.6
Boxes / Pallet	60	60	60	63	63	63
M2 / Boxes	0,52	0.4	0.28	0.48	0.36	0.24
M2 / Pallet	31.2	24	16.8	30.24	22.68	15.12
Pallet / Container	24	24	24	24	24	24
Boxes / Container	1440	1440	1440	1512	1512	1512
M2 / Container	748.8	576	403.2	725.76	544.32	362.88
Load Capacity (TON)	26.5	26.5	28	25.5	25.5	25.5

TECHNICAL DETAILS			
Technical Features	Reference Standard	Our Value	Test Method
Technical Features	± 0,3	Suitable for	ISO 10545-2
Thickness	± 0,5	Suitable for	
Straightness of sides	± 0,3	Suitable for	
Rectangularity	± 0,3	Suitable for	
Surface flatness	c.c. ± 0,4	c.c.± 0,2	ISO 10545-2
	e.c. ± 0,4	e.c. ± 0,2	
	w. ± 0,4	w. ± 0,2	
Water absorption (in% by mass)	EV. ± 0,5 % Individual	EV. ≤ 0,5 %	ISO 10545-3
Breaking strength	S ≥ 1300N	≥ 10000 N	ISO 10545-4
Modulus of rupture	R ₂ N/mm ²	R ≥ 45 N/mm ²	
Impact resistance, as coefficient of restitution	Declared value	≥ = 0,55	ISO 10545-5
Mohs hardness	6	7	EN 101
Resistance to deep abrasion (removed volume)	≤175 mm ²	≤ =150mm ³	ISO 10545-6
Coefficient of thermal linear expansion	Declared value	<= 7MK ⁻¹	ISO 10545-8
Thermal shock resistance	Pass according to EN ISO 10545-1	Resistant	ISO 10545-9
Moisture expansion (in mm/m)	Declared value	≤ 0.01% (0,1mm/m)	ISO 10545-10
Frost resistance	Pass according to EN ISO 10545-1	Resistant	ISO 10545-12
Bond strength/adhesion for improved cementitious adhesives	Declared value	≥ = 1N / mm ² (Class C2- EN 12004)	EN 1348
Fire resistance		non combustable	
Resistance to household chemicals and swimming pool salts	Minimum Class B	A	ISO 10545-13
Resistance to low concentrations of acids and alkalis	Declared Class	LA	
Resistance to high concentrations of acids and alkalis	Declared Class	HA	
Resistance to staining	Declared Class	5	ISO 10545-14
Skid resistance	Dedared value	R11	DIN 51130
Pendulum Friction Test	PTV ≥ 36	≥ 36 Dry ≥ 36 Wet	BS 7976
Coefficient of friction (COF)	u 20,40	≥ 0,40 Dry ≥ 0,40 Wet	B.C.R.A. Rep. CEC/B1



G L O B A L



G L O B A L

R GLOBAL LAYOUT LLP

Near Radheshyam Paper Mill, Lilapar,
Morbi - 363 641, Gujarat, INDIA

+91 840 1410 103  info@rglobal.in  www.rglobal.in

